



BEARINGS(UK)LTD.

50 mm x 90 mm x 20 mm SNR 7210.C.G1UJ84
High precision angular contact ball bearings

Bearing No. 7210.C.G1UJ84

d	50 mm
D	90 mm
B	20 mm
d1	62.45 mm
D1	76.85 mm
D2	83.87 mm
a	19 mm
Contact angle	15 °
rs min	1.1 mm
r1s min	0.6 mm
f0	14.56
Precision class	P4
Mass	0.49 kg
Dynamic load, C	44.8 kN
Static load, C0	34 kN
Fatigue limit load, Cu	1.82 kN
Nlim (oil)	24,000 rpm
Nlim (grease)	15,000 rpm
Axial displacement K Factor	1.21
Preload level	8
Preload value	0.72 kN
Axial rigidity	124 N/ μ m
Radial rigidity	588 N/ μ m
Min operating temperature, Tmin	-30 ° C
Max operating temperature,	120 ° C

7210.C.G1UJ84 Bearing 2D drawings and 3D CAD models



BEARINGS(UK)LTD.

Tmax	
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.34 Hz
Characteristic outer ring frequency, BPF0	6.19 Hz
Characteristic inner ring frequency, BRFI	8.81 Hz
da min	57 mm
db min	57 mm
Da max	83 mm
Db max	83 mm
r1a max	0.6 mm
ra max	1 mm
D6	66.7 mm