



## BEARINGS(UK)LTD.

20 mm x 42 mm x 12 mm NTN  
7004UCG/GNP42U3G High precision angular  
contact ball bearings

Bearing No. 7004UCG/GNP42U3G

d	20 mm
D	42 mm
B	12 mm
d1	28.1 mm
d2	26.4 mm
D1	34.9 mm
D2	38.4 mm
a	10.3 mm
Contact angle	15 °
rs min	0.6 mm
r1s min	0.3 mm
f0	14.1
Precision class	P42
Mass	0.07 kg
Dynamic load, C	11.1 kN
Static load, C0	6.6 kN
Nlim (oil)	59,500 rpm
Nlim (grease)	37,200 rpm
Preload level	GN
Preload value	0.069 kN
Axial rigidity	35.9 N/ μ m
Radial rigidity	192.2 N/ μ m
Min operating temperature, Tmin	-20 ° C
Max operating temperature,	120 ° C

7004UCG/GNP42U3G Bearing 2D drawings and 3D  
CAD models



## BEARINGS(UK)LTD.

Tmax	
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.77 Hz
Characteristic outer ring frequency, BPF0	4.83 Hz
Characteristic inner ring frequency, BRFI	7.17 Hz
da min	24.5 mm
Da max	37.5 mm
Db max	39.5 mm
r1a max	0.3 mm
ra max	0.6 mm
D6	28.6 mm